

## 3T PRACTICE PULLOVER PATTERN

### Midgauge - Tuck Stitch

**Machine:** Mid Gauge 6.5mm

**Yarn:** Any DK with approximately 220yds/ 100 gr (3.5 oz.) skein.

**Gauge:** Approx. 5s/11.5r = 1"

**Tension:** T4 or setting to get gauge

**Stitch pattern:** Any tuck pattern with approximate gauge, either one or 2-color tuck. Remember-this is for practice!

**Notions:** Small bits of contrasting yarn for markers

**Finished Measurements:** Chest (26"), Length (14"), Sleeve Length (11.5")

#### **PATTERN NOTES:**

- If the purl side of the knitting is intended to be the right side of this garment, the Tuck Rib must be removed from the machine with either WY or a garter bar, flipped and rehung on the needles. If the purl side of the knitting is intended to be the right side of this garment, no manipulation is required.
- This garment can be made shorter or longer by adjusting the number of rows between the top of the rib and the armhole marker.

Ronnie's Rib



number of rows

Cast on with waste yarn and knit a few rows. Cast on with main yarn. Set tension dial to MT-2 whole numbers. Knit 1 row. Set carriage ever to "1" or Hold so that needles in hold do not knit. Set needles in a 2x2 arrangement with 2 needles in HOLD and 2 needles in WORKING POSITION. Knit 1 row. Move needles in hold to working position and those that had been in working position to hold. Knit 1 row. Continue switching needle positions every row for desired

#### **Abbreviations**

BO: bind off  
CO: cast on  
St/sts: stitch/stitches  
RW/rws: row/rows  
K: knit  
MY: main yarn  
WY: waste yarn  
RC000: row counter is at zero  
Yds: yards  
RS/WS: right side/wrong side  
PU: pick up  
MT: main tension  
RT: rib tension  
WP: working position  
UWP: upper working position  
NWP: non-working position

## **FRONT**

With WY CO 64sts (32-32). K several rows and 1 rw with nylon cord.

### **RC000**

T2. CO in MY and K 1 rw.  
Set carriage to HOLD .  
K in Ronnie's Rib to **RC10**. COR.

### **RC000**

K 1 rw in SS. Set carriage to **MT**. Load stitch pattern and set carriage to tuck. K to **RC76**.  
Place yarn markers on each side to mark underarm.

K to **RC126**. Place yarn markers on needles L4, R4 and continue to place markers as follows:

**RC128:** L7, R7  
**RC32:** L10, R10  
**RC136:** L11, R11  
**RC140:** L12, 12

K to **RC149:** Place markers on L12, R12  
BO Shoulder sts on each side, then neckline sts.

## **BACK**

Knit as for front to **RC76**. Mark each side for underarm.

K to **RC149:** Place markers on L12, 12  
BO Shoulder sts on each side, then neckline sts

## **SLEEVES (KNIT 2)**

With WY, CO 32sts (16-16). K several rows and 1 rw with nylon cord.

### **RC000**

T2. CO in MY and K 1 rw.

Set carriage to HOLD.

K in Ronnie's Rib to **RC10**. COR.

### **RC000**

K 1 rw in SS. Set carriage to **MT**. Load stitch pattern and set carriage to tuck.

**Knit to RC07. Inc** 1<sup>st</sup> both sides, then **Inc** 1<sup>st</sup> both sides every 7 rws 4 times

**RC35 Inc** 1<sup>st</sup> both sides every 8 rws 10 times

**RC115 Inc** 1<sup>st</sup> both sides. 62 needles in work

**K to RC121**

**Remove Sleeve onto waste yarn or garter bar.**

## **ASSEMBLY**

Sew one shoulder seam. Mark, reinforce and cut and complete neckline as shown in class. Sew remaining shoulder seam. Hang garment between markers on 78 sts, RS facing. With WS facing, hang 78 armhole sts into hooks of needles. Close latched and pull sleeve sts through armhole. BO. Repeat for second sleeve.

Sew side and sleeve seams. Weave in ends. Steam lightly.